

DECLARATION OF PERFORMANCE

DoP N°1 LAMCO HPL COMPACT AE

1. Unique identification code of the product-type: LAMCO HPL COMPACT AE
2. Intended uses: HPL Laminate used as wall and ceiling internal finishes.
3. Manufacturer: LAMICOLOR S.p.A, Via Roma 23 - 12030 Caramagna P.te (CN) – ITALY
4. Authorized representative: N.A.
5. System of AVCP (Assessment and Verification of Constancy of Performance): System 1
6. Harmonized standard: EN 438-7:2005
The notified body: CSI S.p.A. - Viale Lombardia, 20 - 20021 BOLLATE – MI – ITALY - n° 0497 has issued the Certificate of constancy of performance n° 0497/CPR/4579
7. Declared performances:

Essential characteristics	Performance	Harmonized technical specification
Reaction to fire	B-s1,d0 3,0 ≤ thickness (mm) < 6,0 mounted on metallic frame	EN 438-7:2005 section 4.2
Fire resistance	NPD	EN 438-7:2005 section 4.3
Water vapour permeability	NPD	EN 438-7:2005 section 4.4
Resistance to fixings	3 mm – 250 N 4 mm – 1000 N 6 mm – 2000 N	EN 438-7:2005 section 4.5
Direct airborne sound insulation	NPD	EN 438-7:2005 section 4.6
Flexural tensile strenght (suspended ceilings)	Pass	EN 438-7:2005 section 4.8
Thermal resistance/conductivity	NPD	EN 438-7:2005 section 4.9
Release of Formaldehyde	E1	EN 438-7:2005 section 4.11.1
Sound absorption	NPD	EN 438-7:2005 section 4.11.2
Durability	Pass - Resistance to immersion in boiling water: ≥ rating 4 (≥ rating 3 for gloss finish) - Density: ≥ 1,35 g/cm³	EN 438-7:2005 section 4.13.1

8. Appropriate Technical Documentation and/or Specific Technical Documentation: **N.A.**

The performance of product identified above (point 1) is in conformity with the set of declared performances (point 7). This declaration of performance is issued, in accordance with Regulation (EU) N° 305/2011, under the sole responsibility of the manufacturer identified above (point 3).

Signed for and on behalf of the manufacturer by:

Caramagna P.te: 01/07/2026

Roberto Gandino
General Manager

LAMICOLOR S.p.A.
Il Direttore Generale
Roberto Gandino