

DECLARATION OF PERFORMANCE

DoP N°5 LAMCO HPL COMPACT RE STD

1. Unique identification code of the product-type: LAMCO HPL COMPACT RE STD
2. Intended uses: HPL Laminate used as wall and ceiling external finishes
3. Manufacturer: LAMICOLOR S.p.A, Via Roma 23 - 12030 Caramagna P.te (CN) – ITALY
4. Authorized representative: N.A.
5. System of AVCP (Assessment and Verification of Constancy of Performance): System 3
6. Norme harmonisée: EN 438-7:2005
L'organisme notifié : CSI S.p.A. - Viale Lombardia, 20 - 20021 BOLLATE – MI – ITALIE - n° 0497 a
délivré le Certificat d'examen de type n° DE/4595.
7. Declared performances:

Essential characteristics	Performance	Harmonized technical specification
Reaction to fire	C-s1,d0 thickness (mm) ≥ 6,0 mounted on metallic frame	EN 438-7:2005 section 4.2
Fire resistance	NPD	EN 438-7:2005 section 4.3
Water vapour permeability	NPD	EN 438-7:2005 section 4.4
Resistance to fixings	6 mm – 2000 N 8 mm – 3000 N ≥ 10 mm – 4000 N	EN 438-7:2005 section 4.5
Direct airborne sound insulation	NPD	EN 438-7:2005 section 4.6
Flexural tensile strenght (suspended ceilings)	Pass	EN 438-7:2005 section 4.8
Thermal resistance/conductivity	NPD	EN 438-7:2005 section 4.9
Thermal shock resistance	Pass	EN 438-7:2005 section 4.12
Durability	Pass - Resistance to wet conditions: ≥ rating 4 - Density: ≥ 1,35 g/cm ³	EN 438-7:2005 section 4.13.2

8. Appropriate Technical Documentation and/or Specific Technical Documentation: N.A.

The performance of product identified above (point 1) is in conformity with the set of declared performances (point 7). This declaration of performance is issued, in accordance with Regulation (EU) N° 305/2011, under the sole responsibility of the manufacturer identified above (point 3).

Signed for and on behalf of the manufacturer by:

Caramagna P.te: 01/07/2026

Roberto Gandino
General Manager
LAMICOLOR S.p.A.
Il Direttore Generale
Roberto Gandino